

➔ BUSINESS SHREDDER IDEAL 4005

INNOVATIVE HIGH CAPACITY OFFICE SHREDDERS – HIGH PERFORMANCE AND LARGE VOLUME

I "SPS"- (Safety Protection System) package: electronically controlled, transparent safety flap in the feed opening as additional safety element; "EASY_SWITCH" – intelligent control element indicating the operational status of the shredder with varying colour codes and back-lit symbols; automatic reverse and power cut-off in case of a paper jam; automatic stop if the shred bag is full; electronic door protection via a magnetic proximity switch; double motor protection; energy-saving mode after 1 hour **I** photo cell controlled automatic start and stop **I** "ECC" - Electronic Capacity Control – indication of the used sheet capacity during shredding process **I** automatic oil injection on the cutting shafts during shredding operation for constantly high shred performance **I** convenient 405 mm feed opening **I** high quality paper clip proof² cutting shafts from special hardened steel **I** models IDEAL 4005 and IDEAL 4005-C/C suitable for safe shredding of CDs **I** 5 years guarantee² on the cutting shafts **I** quiet but powerful 1600 Watt single phase motor for continuous operation **I** dust-proof gear box housing **I** high-quality wooden cabinet, mobile on castors **I** plastic bag suspension with pull-out mechanism on wheels for easy removal of the full bag (models M/C and SM/C with shred container) **I** approx. 225 litres volume for the shreds

Power connection³: 230 V / 50 Hz / 1~, Dimensions (H x W x D): 1010 x 640 x 590 mm, Weight: 115 kg



"ECC" CONTROL



..ECC" – Electronic Capacity Control: for continuous feeding without creating paper jams the used sheet capacity is indicated during the shredding process.

➔ IDEAL 4005

Shred width	6 mm
Sheet capacity ¹	50-55 42-47
Security level	2
Feed opening	405 mm
Motor capacity	1600 Watt

➔ IDEAL 4005-C/C

Particle size	4 x 40 mm
Sheet capacity ¹	40-45 34-39
Security level	3
Feed opening	405 mm
Motor capacity	1600 Watt

➔ IDEAL 4005-C/C

Particle size	2 x 15 mm
Sheet capacity ¹	25-30 21-26
Security level	4
Feed opening	405 mm
Motor capacity	1600 Watt

➔ IDEAL 4005-M/C

Particle size	0.8 x 12 mm
Sheet capacity ¹	15-17 13-15
Security level	5
Feed opening	405 mm
Motor capacity	1600 Watt

➔ IDEAL 4005-SM/C

Particle size	0.8 x 5 mm
Sheet capacity ¹	10-11 8-9
Security level	"Level 6"
Feed opening	405 mm
Motor capacity	1600 Watt



L.T.E. Listed 802 D

¹ A4 paper, 70 g/m² | 80 g/m²

² 4005-M/C 0.8 x 12 mm and 4005-SM/C 0.8 x 5 mm: Paper clips and staples have to be removed before shredding. Guarantee 1 year.

³ other voltages available

➔ BUSINESS SHREDDER IDEAL 4005 + ACCESSORIES

MODEL	ARTICLE NO.	EAN CODE
IDEAL 4005, 6 mm 230 V, 50 Hz*	40056111	4019364681110
IDEAL 4005-C/C, 4 x 40 mm 230 V, 50 Hz*	40059111	4019364683114
IDEAL 4005-C/C, 2 x 15 mm 230 V, 50 Hz*	40051111	4019364682117
IDEAL 4005-M/C, 0.8 x 12 mm 230 V, 50 Hz*	40058111	4019364684111
IDEAL 4005-SM/C, 0.8 x 5 mm 230 V, 50 Hz*	40057111	4019364684517
Plastic bags for IDEAL 4005 (50 pieces per packing unit)	9000410	4019364940705
Shredder oil for IDEAL 4005 (5 x 1 litre per packing unit)	9000620	4019364950858

* other voltages available

TRANSPARENT SAFETY FLAP




The safety flap in the feed opening is an additional safety element to keep fingers, ties or other objects away from the cutting shafts.

"EASY_SWITCH"



Intelligent multifunction switch element with integrated optical signals for the operational status.

AUTOMATIC OIL INJECTION



The automatic oil injection system lubricates the cutting shafts when shredding and guarantees a constantly high shred performance.

PLASTIC BAG SUSPENSION



The plastic bag suspension on wheels allows an easy and convenient removal of the full shred bag.